



Distributed by







Refrigerator and Freezer
Thermometers

Measuring Success Since 1885

Foodservice Catalog

Refrigerator / Freezer Thermometers

	25HP-01	330-0	335-01	336-01	535-01
Temperature Range:	-20° to 80°F -29° to 27°C	-40° to 120°F -40° to 50°C	-40° to 80°F -40° to 25°C	-40° to 100°F -40° to 40°C	-20° to 120°F -30° to 50°C
Accuracy:	±2°F / ±1°C	±2°F / ±1°C	±2°F / ±1°C	±2°F / ±1°C	±5°F / ±2°C
Housing Material:	Stainless Steel	Food Grade Plastic	Stainless Steel	Food Grade Plastic	Plastic
Dimensions:	2.375" x 1.5" x 3" 60 x 38 x 76 mm	.625" x .25" x 4" 16 x 6.4 x 102 mm	4.75" x .875" x 1.125" 120.6 x 22 x 29 mm	6" x 1" 152.4 x 25.4 mm	2" 50.8 mm
Lens Material:	Glass	-	Crystal Clear Polycarbonate	-	Plastic
Weight:	1.5 oz / 43 g	.25 oz / 7 g	1 oz / 28 g	2 oz / 57 g	.5 oz / 14 g
Regulatory Listings:					-
Warranty:	1 Year	1 Year	1 Year	1 Year	1 Year



335
Refrigerator / Freezer Thermometer

Use the cooler thermometer's magnetic back or self adhesive tabs for mounting to the underside of refrigerated glass cases.



535
2" Cooler Thermometer

ColdStik™ Product Simulator

The ColdStik™ doesn't just measure the air, it is a food product simulator. It takes on the food product temperature in changing ambient conditions of any refrigerator, freezer, walk-in or delivery truck. It helps operators to conserve energy, when the refrigeration temperature is adjusted for the actual product temperature food loss and energy expenses are reduced.



25HP
Refrigerator / Freezer Thermometer



336-01
ColdStik™ Product Simulator



Refrigerator / Freezer Thermometers

Cooper
ATKINS

**PERFORMANCE
THAT LASTS**

**HVAC/R
OEM
INDUSTRIAL**

The advertisement features a background image of a large, modern building with a glass facade. In the foreground, there are several pieces of equipment: a large blue and yellow unit, a smaller blue unit with a digital display, a black handheld device, and a red and black unit. The text 'PERFORMANCE THAT LASTS' is written in large, bold, red letters across the middle of the image.

Thermocouple Probe Catalog

Cooper
ATKINS

Table of Contents

Probe Index & Guide Information	2
Standard Needle Probes	3
Heavy Duty Needle Probes	4
High Temperature Needle Probes	4
Fast Fix Needle Probes	4
Set Probes	5-6
Air Probes	6-7
Surface Probes	7-8
Immersion Probes	8-9
Replacement Probes for 230 Series Thermocouple Immersion Instruments	10
Replacement Probes for 230-047 Thermocouple Immersion Instruments	11
Connectors and Accessories	12
Probe Wires	13

COOPER-ATKINS Enterprises
125
YEARS
1890-2015

New Atkins
New! Reusable Thermocouple Probes 2015



Many complex circuit designs that use calculated values in the equations within their calculators have become a thing of the past. We are so committed to ensuring the accuracy of our products that we guarantee it.

[illegible]

PROFESSIONAL FOODSERVICE KITCHEN PRODUCTS

1. 2297 Pry Bar Probe	3. 3600K Assault Fry Fry Thermocouple Instrument	5. 3270 TC6	7. 13100 Probe Wipes - Large Tub 300 Count	9. 13154 Probe Wipes - Mini 250 90 Hour Digital Timer	11. 9124 Single Surface 24 Hour Digital Timer	13. 91230K EcoTemp™ Thermocouple Instrument with Dual Beep Probe and Wall Bracket	15. 1191122M Mini Thermometer Hygrometer	17. 131306 CoolSafe™ Refrigerator / Freezer Thermometer	19. 14. 330 Refrigerator / Freezer Thermometer	21. 536 Reach-In Cooler Thermometer	23. 330K Glass Tube Refrigerator / Freezer Thermometer	25. 294P In-Meal Refrigerator / Freezer Thermometer	27. 131450W Digital Pocket Test Thermometer w/ Temp Alarm	29. 131450W Pen Style Digital Pocket Test Thermometer	31. 5031A-K Vegetable Guided Probe	33. 246P Oven Thermometer	35. 3210 Grid Surface Thermometer	37. 5362K Patty Probe 60° Angle 3/16" Depth	39. 131459 Pocket Test Run-In Digital Thermometer	41. 3200 Mechanical Pocket Test, 0° - 220°F	43. 30332 Aquafil™ Wobble-Bow™ Thermocouple Instrument with Duranide Probe	45. 27. 017361 Digital Cooking Thermometer / Timer with Temperature Alarm and Probe	47. 328 Meat Thermometer	49. 328 Paddle Style Deep Fry / Candy / Jelly Thermometer	51. 328 Deep Fry / Candy / Jelly Thermometer	53. 328 Long Range Mechanical Thermometer	55. 317602 Long Range Digital Pocket Test Thermometer	57. 317602 CoolSafe™ Refrigerator / Freezer Thermometer	59. 3481 IF Stem Test Thermometer	61. 3481 Dual Temp™ Infrared Thermometer with RTD Probe	63. 3482 Slim-Line Infrared Thermometer	65. 37. 412 Gun Style Infrared Thermometer w/ Laser	67. 38. 470 Mini Infrared Thermometer
--------------------------	---	----------------	---	--	--	--	---	--	---	--	---	--	--	--	---------------------------------------	------------------------------	--------------------------------------	--	--	--	---	--	-----------------------------	--	---	--	--	--	--------------------------------------	--	--	--	--

Cooper
ATKINS®

Cooper-Atkins Corporation, 33 Reeds Gap Road, Middlefield, CT 06455 U.S.A.
800-835-5011 • 860-347-2256 • Fax: 860-347-5135 • www.cooper-atkins.com • info@cooper-atkins.com

07-1548

FOODSERVICE CRITICAL TEMPERATURE CHART

FOODS are assessed according to factors that can cause food to become harmful. Some factors may not be determined by temperature.

REHEATING:

- Reheat food to a minimum temperature of 165°F (74°C)
- Reheat all temperature held below 135°F (57°C)

UPPER CASE

HOT HOLDING: 135°F (57°C) or above

- Keep food hot
- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch hot holding equipment in heat hold

TCR

DANGER ZONE: 41°F (5°C) to 135°F (57°C)

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COLD HOLDING: 41°F (5°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

FREEZER: Maximum Freezer Temp: 0°F (-18°C) or below.

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

250R

COOLING: 135°F (57°C) or below

- Do not touch handles
- Do not touch the probe
- Do not touch as a thermometer reading
- Do not touch as a thermometer reading

67-968-75M-0311